



2-Post Overhead Lift Comparison Guide



Atlas 9KOH



Atlas 90HSC (SS)

	Atlas 9KOH	Atlas 90HSC (SS)
Capacity	9,000 LBS.	9,000 LBS.
Arm Capacity	2,250 LBS. Per Arm	2,250 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	1 Piece (Non-Adjustable) Symmetrical
Overall Height	142" (11' 10") or 138" (11' 6")	142" (11' 10")
Overall Width	134 1/4" (11' 2 1/4")	132" (11')
Maximum Lift Height (With Truck Adapters)	80 1/4" (6' 8 1/4")	81 3/8" (6' 9 3/8")
Cylinder Configuration	Chain Over Roller	Chain Over Roller
Arm Configuration	Asymmetric	Super-Symmetrical
Lock Release	Dual Point	Single Point
Between Columns	109 3/4" (9' 1 3/4")	109 1/2" (9' 1 1/2")
Drive Thru	92 1/2" (7' 8 1/2")	100 3/4" (8' 4 3/4")
Power Requirements	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	5mm
Minimum Arm Height	4"	4 1/2"
Truck Adapters	8 Piece Set (2 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	2 yr. Structural, 1 yr. Hyd.	5 yr. Structural, 1 yr. Hyd.
Shipping Weight	1,474 LB.	1,404 LBS.

* Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas PV-9P



Atlas PV-9HP



Atlas PV-9WP

Capacity	9,000 LB.	9,000 LBS.	9,000 LB.
Arm Capacity	2,500 LBS. Per Arm	2,250 LBS. Per Arm	2,250 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	142 ½" (11' 10 ½") or 150 ½" (12' 6 ½")	166 ½" (13' 10 1/2") or 174 ½" (14' 6 1/2")	142 1/2" (11' 10 1/2") or 150 1/2" (12' 6 1/2")
Overall Width	135" (11' 3")	135" (11' 3")	141" (11' 9")
Maximum Lift Height (With Truck Adapters)	80 ½" (6' 8 ½")	80 ½" (6' 8 ½")	80 ½" (6' 8 ½")
Cylinder Configuration	Direct Drive	Direct Drive	Direct Drive
Arm Configuration	Asymmetric/Symmetrical	Asymmetric/Symmetrical	Asymmetric/Symmetrical
Lock Release	Single Point	Single Point	Single Point
Between Columns	112 ¼" (9' 4 ¼")	112 ¼" (9' 4 ¼")	118 1/4" (9' 10 1/4")
Drive Thru	99 ½" (8' 3 ½") - Symmetric 93" (7' 9") - Asymmetric	99 ½" (8' 3 ½") - Symmetric 93" (7' 9") - Asymmetric	105 ½" (8' 9 ½") - Symmetric 99" (8' 3") - Asymmetric
Power Requirements	220V, 1 Phase	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	5mm	5mm
Minimum Arm Height	4 1/2"	4 1/2"	4 1/2"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	1,500 LBS.	1,600 LBS.	1,528 LBS.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas OH-10X



Atlas PV-10P



Atlas PV-10HP

	Atlas OH-10X	Atlas PV-10P	Atlas PV-10HP
Capacity	10,000 LB.	10,000 LB.	10,000 LB.
Arm Capacity	2,500 LBS. Per Arm	2,500 LBS. Per Arm	2,500 LBS. Per Arm
Column Configuration	1 Piece (Non-Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	151 1/2" (12' 7 1/2")	142" (11' 10") or 146" (12' 2")	166" (13' 10") or 170" (14' 2")
Height To Shut Off Bar	144" (12')	136" (11' 4")* LOW 140" (11' 8") HIGH	160" (13' 4")* LOW 164" (13' 8") HIGH
Overall Width	144 5/8" (12' 5/8")	137 1/2" (11' 5 1/2")	137 1/2" (11' 5 1/2")
Maximum Lift Height (With Truck Adapters)	84" (7')	82" (6' 10")	82" (6' 10")
Cylinder Configuration	Direct Drive	Direct Drive	Direct Drive
Arm Configuration	Symmetric	Asymmetric/Symmetric	Asymmetric/Symmetric
Lock Release	Single Point	Single Point	Single Point
Between Columns	117 1/2" (9' 9 1/2")	110" (9' 2")	110" (9' 2")
Drive Thru	106 1/8"	96" (8')	96" (8')
Power Requirements	220V, 1 Phase	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	6mm	6mm
Minimum Arm Height	4"	4 1/2"	4 1/2"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	1,665 LBS.	1,875 LBS.	2,150 LBS.

*Purchase the purchase of additional shorter cables.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas Apex-10 Plus



Atlas Apex-10H Plus

Capacity	10,000 LBS.	10,000 LBS.
Arm Capacity	2,500 LBS. Per Arm	2,500 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Asymmetrical OR Symmetrical	2 Piece (Adjustable) Asymmetrical OR Symmetrical
Overall Height	135 7/8" (11' 3 7/8")** or 139 7/8" (11' 7 7/8") 142 1/2" (11' 10 1/2") [Height With Cylinder]	160" (13' 4")** LOW 164" (13' 8") HIGH
Height To Shut Off Bar	130 1/4" (10' 10 1/4")** or 134 1/4" (11' 2 1/4")	154" (12' 10")** LOW 158" (13' 2") HIGH
Overall Width	139" (11' 7") Asymmetrical 135 1/4" (11' 3 1/4") Symmetrical	139" (11' 7") Asymmetrical 135 1/4" (11' 3 1/4") Symmetrical
Maximum Lift Height (With Truck Adapters)	81 1/2" (6' 9 1/2")	81 1/2" (6' 9 1/2")
Cylinder Configuration	Direct Drive	Direct Drive
Arm Configuration	Asymmetric/Symmetric	Asymmetric/Symmetric
Lock Release	Single Point	Single Point
Between Columns	107 3/4" (8' 11 3/4") Asymmetrical 112 1/2" (9' 4 1/2") Symmetrical	107 3/4" (8' 11 3/4") Asymmetrical 112 1/2" (9' 4 1/2") Symmetrical
Drive Thru	91" (7' 7") Asymmetrical 99 1/2" (8' 3 1/2") Symmetrical	91" (7' 7") Asymmetrical 99 1/2" (8' 3 1/2") Symmetrical
Power Requirements	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	6mm	6mm
Minimum Arm Height	4 1/2"	4 1/2"
Truck Adapters	8 Piece Set (2 Per Arm) With 4 Screw-Up Lift Pads	8 Piece Set (2 Per Arm) With 4 Screw-Up Lift Pads
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	1,750 LBS.	1,850 LBS.

** Requires installation of spacers. See manual for instructions.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas PV-12P



Atlas PV-15P

Capacity	12,000 LBS.	15,000 LBS.
Arm Capacity	3,000 LBS. Per Arm	3,750 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	148 1/2" (12' 4 1/2")* LOW 163 1/2" (13' 7 1/2") MIDDLE 175 1/2" (14' 7 1/2") HIGH	150 3/8" (12' 6 3/8")* LOW 162 3/8" (13' 6 3/8") MIDDLE 177 3/8" (14' 9 3/8") HIGH
Height To Shut Off Bar	142" (11' 10")* LOW 157" (13' 1") MIDDLE 169" (14' 1") HIGH	140 3/4" (11' 8 3/4")* LOW 152 3/4" (12' 8 3/4") MIDDLE 167 3/4" (13' 11 3/4") HIGH
Overall Width	158" (13' 2")	158" (13' 2")
Maximum Lift Height (With Truck Adapters)	82" (6' 10")	79 3/4" (6' 7 3/4")
Cylinder Configuration	Direct Drive	Direct Drive
Arm Configuration	Symmetrical	Symmetrical
Lock Release	Single Point	Single Point
Between Columns	122 5/8" (10' 2 5/8")	122 7/8" (10' 2 7/8")
Drive Thru	108 5/8" (9' 5/8")	109" (9' 1")
Power Requirements	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	6mm	6mm
Minimum Arm Height	4 1/2"	6 5/8"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	2,100 LB.	2,600 LB.

*Purchase the purchase of additional shorter cables.

Manufacturing specifications subject to change.