



2-Post Overhead Lift Comparison Guide



	Atlas 9KOH	Atlas 90HSC (SS)
Capacity	9,000 LBS.	9,000 LBS.
Arm Capacity	2,250 LBS. Per Arm	2,250 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	1 Piece (Non-Adjustable) Symmetrical
Overall Height	142" (11' 10") or 138" (11' 6")	142" (11' 10")
Overall Width	134 1/4" (11' 2 1/4")	132" (11')
Maximum Lift Height (With Truck Adapters)	80 1/4" (6' 8 1/4")	81 3/8" (6' 9 3/8")
Cylinder Configuration	Chain Over Roller	Chain Over Roller
Arm Configuration	Asymmetric	Super-Symmetrical
Lock Release	Dual Point	Single Point
Between Columns	109 3/4" (9' 1 3/4")	109 1/2" (9' 1 1/2")
Drive Thru	92 1/2" (7' 8 1/2")	100 3/4" (8' 4 3/4")
Power Requirements	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	5mm
Minimum Arm Height	4"	4 1/2"
Truck Adapters	8 Piece Set (2 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	2 yr. Structural, 1 yr. Hyd.	5 yr. Structural, 1 yr. Hyd.
Shipping Weight	1,474 LB.	1,404 LBS.

* Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas PV-9P



Atlas PV-9HP





Atlas PV-9WP

Capacity	9,000 LB.	9,000 LBS.	9,000 LB.
Arm Capacity	2,500 LBS. Per Arm	2,250 LBS. Per Arm	2,250 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	142 ½" (11' 10 ½") or 150 ½" (12' 6 ½")	166 ½" (13' 10 1/2") or 174 ½" (14' 6 1/2")	142 1/2" (11' 10 1/2") or 150 1/2" (12' 6 1/2")
Overall Width	135" (11' 3")	135" (11' 3")	141" (11' 9")
Maximum Lift Height (With Truck Adapters)	80 ½" (6' 8 ½")	80 ½" (6' 8 ½")	80 ½" (6' 8 ½")
Cylinder Configuration	Direct Drive	Direct Drive	Direct Drive
Arm Configuration	Asymmetric/Symmetric	Asymmetric/Symmetric	Asymmetric/Symmetric
Lock Release	Single Point	Single Point	Single Point
Between Columns	112 ¼" (9' 4 ¼")	112 ¼" (9' 4 ¼")	118 1/4" (9' 10 1/4")
Drive Thru	99 ½" (8' 3 ½") - Symmetric 93" (7' 9") - Asymmetric	99 ½" (8' 3 ½") - Symmetric 93" (7' 9") - Asymmetric	105 ½" (8' 9 ½") - Symmetric 99" (8' 3") - Asymmetric
Power Requirements	220V, 1 Phase	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	5mm	5mm
Minimum Arm Height	4 1/2"	4 1/2"	4 1/2"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	1,500 LBS.	1,600 LBS.	1,528 LBS.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide

			
	Atlas OH-10X	Atlas PV-10P	Atlas PV-10HP
Capacity	10,000 LB.	10,000 LB.	10,000 LB.
Arm Capacity	2,500 LBS. Per Arm	2,500 LBS. Per Arm	2,500 LBS. Per Arm
Column Configuration	1 Piece (Non-Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	151 1/2" (12' 7 1/2")	142" (11' 10") or 146" (12' 2")	166" (13' 10") or 170" (14' 2")
Height To Shut Off Bar	144" (12')	136" (11' 4")* LOW 140" (11' 8") HIGH	160" (13' 4")* LOW 164" (13' 8") HIGH
Overall Width	144 5/8" (12' 5/8")	137 1/2" (11' 5 1/2")	137 1/2" (11' 5 1/2")
Maximum Lift Height (With Truck Adapters)	84" (7')	82" (6' 10")	82" (6' 10")
Cylinder Configuration	Direct Drive	Direct Drive	Direct Drive
Arm Configuration	Symmetric	Asymmetric/Symmetric	Asymmetric/Symmetric
Lock Release	Single Point	Single Point	Single Point
Between Columns	117 1/2" (9' 9 1/2")	110" (9' 2")	110" (9' 2")
Drive Thru	106 1/8"	96" (8')	96" (8')
Power Requirements	220V, 1 Phase	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	5mm	6mm	6mm
Minimum Arm Height	4"	4 1/2"	4 1/2"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	1,665 LBS.	1,875 LBS.	2,150 LBS.

*Purchase the purchase of additional shorter cables.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide

			
	Atlas Apex-10 Plus	Atlas Apex-10H Plus	Atlas Elite 10X
Capacity	10,000 LBS.	10,000 LBS.	10,000 LBS.
Arm Capacity	2,500 LBS. Per Arm	2,500 LBS. Per Arm	2,500 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Asymmetrical OR Symmetrical	2 Piece (Adjustable) Asymmetrical OR Symmetrical	2 Piece (Adjustable) Super Symmetrical
Overall Height	135 7/8" (11' 3 7/8")** LOW or 139 7/8" (11' 7 7/8") HIGH 142 1/2" (11' 10 1/2") [Height With Cylinder]	160" (13' 4")** LOW 164" (13' 8") HIGH	143" (11' 11") LOW 148 3/4" (12' 4 3/4") HIGH
Height To Shut Off Bar	130 1/4" (10' 10 1/4")** LOW or 134 1/4" (11' 2 1/4") HIGH	154" (12' 10")** LOW 158" (13' 2") HIGH	138 3/8" (10' 10 1/4") LOW 144 1/8" (12' 1/8") HIGH
Overall Width	139" (11' 7") Asymmetrical 135 1/4" (11' 3 1/4") Symmetrical	139" (11' 7") Asymmetrical 135 1/4" (11' 3 1/4") Symmetrical	136 1/2" (11' 4 1/2")
Maximum Lift Height (With Truck Adapters)	81 1/2" (6' 9 1/2")	81 1/2" (6' 9 1/2")	76 1/2" (6' 4 1/2")
Cylinder Configuration	Direct Drive	Direct Drive	Direct Drive
Arm Configuration	Asymmetric/Symmetric	Asymmetric/Symmetric	Super Symmetric
Lock Release	Single Point	Single Point	Single Point
Between Columns	107 3/4" (8' 11 3/4") Asymmetrical 112 1/2" (9' 4 1/2") Symmetrical	107 3/4" (8' 11 3/4") Asymmetrical 112 1/2" (9' 4 1/2") Symmetrical	109 3/4" (9' 1 3/4")
Drive Thru	91" (7' 7") Asymmetrical 99 1/2" (8' 3 1/2") Symmetrical	91" (7' 7") Asymmetrical 99 1/2" (8' 3 1/2") Symmetrical	98 3/4" (8' 2 3/4")
Power Requirements	220V, 1 Phase	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	6mm	6mm	6mm
Minimum Arm Height	4 1/2"	4 1/2"	4 1/2"
Truck Adapters	8 Piece Set (2 Per Arm) With 4 Screw-Up Lift Pads	8 Piece Set (2 Per Arm) With 4 Screw-Up Lift Pads	4 Piece Set With 4 Double Screw-Up Lift Pads
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.	1 yr. Structural, 1 yr. Hyd.
Shipping Weight	1,750 LBS.	1,850 LBS.	1,800 LBS.

** Requires installation of spacers. See manual for instructions.

Manufacturing specifications subject to change.



2-Post Overhead Lift Comparison Guide



Atlas PV-12P



Atlas PV-15P

Capacity	12,000 LBS.	15,000 LBS.
Arm Capacity	3,000 LBS. Per Arm	3,750 LBS. Per Arm
Column Configuration	2 Piece (Adjustable) Symmetrical	2 Piece (Adjustable) Symmetrical
Overall Height	148 1/2" (12' 4 1/2")* LOW 163 1/2" (13' 7 1/2") MIDDLE 175 1/2" (14' 7 1/2") HIGH	150 3/8" (12' 6 3/8")* LOW 162 3/8" (13' 6 3/8") MIDDLE 177 3/8" (14' 9 3/8") HIGH
Height To Shut Off Bar	142" (11' 10")* LOW 157" (13' 1") MIDDLE 169" (14' 1") HIGH	140 3/4" (11' 8 3/4")* LOW 152 3/4" (12' 8 3/4") MIDDLE 167 3/4" (13' 11 3/4") HIGH
Overall Width	158" (13' 2")	158" (13' 2")
Maximum Lift Height (With Truck Adapters)	82" (6' 10")	79 3/4" (6' 7 3/4")
Cylinder Configuration	Direct Drive	Direct Drive
Arm Configuration	Symmetrical	Symmetrical
Lock Release	Single Point	Single Point
Between Columns	122 5/8" (10' 2 5/8")	122 7/8" (10' 2 7/8")
Drive Thru	108 5/8" (9' 5/8")	109" (9' 1")
Power Requirements	220V, 1 Phase	220V, 1 Phase
Column Thickness of Steel	6mm	6mm
Minimum Arm Height	4 1/2"	6 5/8"
Truck Adapters	12 Piece Set (3 Per Arm)	12 Piece Set (3 Per Arm)
Warranty	5 yr. Structural, 2 yr. Hyd.	5 yr. Structural, 2 yr. Hyd.
Shipping Weight	2,100 LB.	2,600 LB.

*Purchase the purchase of additional shorter cables.

Manufacturing specifications subject to change.