



## 4-Post Lift Comparison Guide



	Atlas Garage Pro 8000	Atlas Garage Pro 8000 EXT	Atlas Garage Pro 8000 EXT-L	Atlas Garage Pro 8K XLT	Atlas 408-SL
Capacity	8,000 LB	8,000 LB	8,000 LB	8,000 LB	8,000 LB
Lifting Height	72" (6')	84 1/4" (7' 1/4")	84 1/2" (7' 1/2")	82 1/4" (6' 10 1/4")	69 3/4" (5' 9 3/4")
Overall Width of Columns (With Motor)	114" (9' 6")	114" (9' 6")	116 1/2" (9' 8 1/2")	119" (9' 11")	106 5/8" (8' 10 5/8")
Overall Length (w/ Approach Ramps)	207 1/2" (17' 3 1/2")	207 1/2" (17' 3 1/2")	227" (18' 11")	222 1/2" (18' 6 1/2")	208" (17' 4")
Length Between Columns	157 1/2" (13' 1 1/2")	157 1/2" (13' 1 1/2")	176 1/2" (14' 8 1/2")	172 1/4" (14' 4 1/4")	156" (13')
Runway Length	165 1/2" (13' 9 1/2")	165 1/2" (13' 9 1/2")	185 1/2" (15' 5 1/2")	180 1/2" (15' 1/2")	166 3/4" (13' 10 3/4")
Runway Width	21 1/4" (1' 9 1/4")	21 1/4" (1' 9 1/4")	22" (1' 10")	20 1/4" (1' 8 1/4")	20" (1' 8")
Thickness of Runway	4 1/2"	4 1/2"	4 1/2"	4 1/2"	4 3/4"
Width Between Runways	37 3/8"	37 3/8"	38"	43"	37" (3' 1")
Width Between Runway Rails	31 3/4"	31 3/4"	34"	39 1/4"	34 3/8" (2' 10 3/8")
Outside Runway to Outside Runway	74 3/4" (6' 2 3/4")	74 3/4" (6' 2 3/4")	77 3/4" (6' 5 3/4")	81" (6' 9")	74 1/2" (6' 2 1/2")
Clearance Under Runways	67 1/2" (5' 7 1/2")	79" (6' 7")	80" (6' 8")	77 15/16" (6' 5 15/16")	65" (5' 5")
Clearance Between Columns	94 1/2" (7' 10 1/2")	94 1/2" (7' 10 1/2")	98" (8' 2")	100 5/16" (8' 4 5/16")	95 1/2" (7' 11 1/2")
Height of Columns	83" (6' 11")	98 1/2" (8' 2 1/2")	97 1/2" (8' 1 1/2")	94 3/8" (7' 10 3/8")	83" (6' 11")
Maximum Wheel Base	153 1/2" (12' 9 1/2")	153 1/2" (12' 9 1/2")	173" (14' 5")	178" (14' 10")	159" (13' 3")
Drive Thru	80 1/2" (6' 8 1/2")	80 1/2" (6' 8 1/2")	84" (7')	86 1/2" (7' 2 1/2")	82" (6' 10")
Motor	110V	110V	110V	110V	110V
Warranty	2 Year Structural, 1 Year Hydraulic	2 Year Structural, 1 Year Hydraulic	2 Year Structural, 1 Year Hydraulic	1 Year Structural, 1 Year Hydraulic	2 Year Structural, 2 Year Hydraulic
Shipping Weight	1,720 LB.	1,739 LB.	1,900 LB.	1,914 LB.	1,965 LB.

Manufacturing specifications subject to change.



## 4-Post Lift Comparison Guide



	Atlas 409-HP	Atlas Garage Pro 9,000	Atlas 412	Atlas 414
Capacity	9,000 LB	9,000 LB	12,000 LB.	14,000 LB.
Lifting Height	81 1/2" (6' 9 1/2")	85" (7' 1")	74" (6' 2")	74" (6' 2")
Overall Width of Columns (With Motor)	134 1/4" (11' 2 1/4")	131 1/2" (10' 11 1/2")	135" (11' 3")	142" (11' 10")
Overall Length (w/ Approach Ramps)	231 3/4" (19' 3 3/4")	232" (19' 4")	230" (19' 2")	256 1/2" (21' 4 1/2")
Length Between Columns	179 3/4" (14' 11 3/4")	184 1/2" (15' 4 1/2")	184 1/4" (15' 4 1/4")	196 3/4" (16' 4 3/4")
Runway Length	190" (15' 10")	199 1/2" (16' 7 1/2")	186 1/2" (15' 6 1/2")	207" (17' 3")
Runway Width	21 3/4" (1' 9 3/4")	21 1/4" (1' 9 1/4")	22" (1' 10")	22" (1' 10")
Thickness of Runway	5 1/2"	4 3/4"	5 1/2"	6 1/2"
Width Between Runways	42 1/4" (3' 6 1/4")	39 1/4" (3' 3 1/4")	44 1/2" (3' 8 1/2")	44" (3' 8") *
Width Between Runway Rails	38 3/4" (3' 2 3/4")	35 1/2" (2' 11 1/2")	42" (3' 6")	40 3/8" (3' 4 3/8") *
Outside Runway to Outside Runway	82 1/4" (6' 10 1/4")	79" (6' 7")	84 3/4" (7' 3/4")	83 5/8" (6' 11 5/8") *
Clearance Under Runways	76" (6' 4")	80 1/2" (6' 8 1/2")	68 1/2" (5' 8 1/2")	67 1/2" (5' 7 1/2")
Clearance Between columns	112 1/2" (9' 4 1/2")	110 1/2" (9' 2 1/2")	112 1/4" (9' 4 1/4")	116" (9' 8")
Height of Columns	94 3/4" (7' 10 3/4")	95 3/4" (7' 11 3/4")	82" (6' 10")	86" (7' 2")
Maximum Wheel Base	178" (14' 10")	187" (15' 7")	175" (14' 7")	186" (15' 6")
Drive Thru	98" (8' 2")	97 1/4" (8' 1 1/4")	98 1/2" (8' 2 1/2")	102" (8' 6")
Motor	110V	110V	220V 1 Phase	220V 1 Phase
Warranty	2 Year Structural, 2 Year Hydraulic	2 Year Structural, 1 Year Hydraulic	5 Year Structural, 2 Year Hydraulic	5 Year Structural, 2 Year Hydraulic
Shipping Weight	2,230 LBS.	2,300 LBS.	2,400 LBS.	3,200 LBS.

\*Measurement may vary due to adjustable runway.

Manufacturing specifications subject to change.



## 4-Post Lift Comparison Guide



	Atlas 412A	Atlas 414A	Atlas 14KOF	Atlas 14KOF-EXT
Capacity	12,000 LB.	14,000 LB.	14,000 LB.	14,000 LB.
Lifting Height	76 1/4" (6' 4 1/4")	76 1/4" (6' 4 1/4")	69 7/8" (5' 9 7/8")	69 7/8" (5' 9 7/8")
Overall Width of Columns (With Motor)	135" (11' 3")	142" (11' 10")	138" (11' 6")	138" (11' 6")
Overall Length (w/ Approach Ramps)	230" (19' 2")	256 1/2" (21' 4 1/2")	257 1/2" (21' 5 1/2")	280" (23' 4")
4-Wheel Alignment Wheelbase	Maximum 154" (12' 10") Minimum 82" (6' 10")	Maximum 172 1/2" (14' 4 1/2") Minimum 96" (8')	Maximum 162" (13' 6") Minimum 81" (6' 9")	Maximum 162" (13' 6") Minimum 81" (6' 9")
2-Wheel Alignment Wheelbase	Maximum 157" (13' 1")	Maximum 175 1/2" (14' 7 1/2")	Maximum 178" (14' 10")	Maximum 187" (15' 7") Minimum 81" (6' 9")
Length Between Columns	184 1/4" (15' 4 1/4")	196 3/4" (16' 4 3/4")	215 1/2" (17' 11 1/2")	239" (19' 11")
Runway Length	186 1/2" (15' 6 1/2")	198 1/4" (16' 6 1/4")	199" (16' 7")	223" (18' 7")
Runway Width	22" (1' 10")	22" (1' 10")	19 3/4" (1' 7 3/4")	19 3/4"
Thickness of Runway	7 3/4"	8 3/4"	8 3/8"	8 3/8"
Width Between Runways	44 1/2" (3' 8 1/2")	44" (3' 8") *	42 5/8" (3' 6 5/8")	42 5/8" (3' 6 5/8")
Width Between Runway Rails	42" (3' 6")	40 3/8" (3' 4 3/8") *	39 1/8" (3' 3 1/8")	39 1/8" (3' 3 1/8")
Outside Runway to Outside Runway	84 3/4" (7' 3/4")	83 5/8" (6' 11 5/8") *	82 1/2" (6' 10 1/2")	82 1/2" (6' 10 1/2")
Clearance Under Runways	68 1/2" (5' 8 1/2")	67 1/2" (5' 7 1/2")	61 1/2" (5' 1 1/2")	61 1/2" (5' 1 1/2")
Clearance Between columns	112 1/4" (9' 4 1/4")	116" (9' 8")	Rear: 113 7/8" (9' 5 7/8") Front: 110 1/8" (9' 2 1/8")	Rear: 113 7/8" (9' 5 7/8") Front: 110 1/8" (9' 2 1/8")
Height of Columns	82" (6' 10")	86" (7' 2")	Rear: 89" (7' 5") Front: 99 3/4" (8' 3 3/4")	Rear: 89" (7' 5") Front: 99 3/4" (8' 3 3/4")
Maximum Wheel Base	175" (14' 7")	186" (15' 6")	190" (15' 10")	199" (16' 7")
Drive Thru	98 1/2" (8' 2 1/2")	102" (8' 6")	99" (8' 3")	99" (8' 3")
Motor	220V 1 Phase	220V 1 Phase	220V 1 Phase	220V 1 Phase
Warranty	5 Year Structural, 2 Year Hydraulic	5 Year Structural, 2 Year Hydraulic	2 Year Structural, 1 Year Hydraulic	2 Year Structural, 1 Year Hydraulic
Shipping Weight	2,700 LB.	3,500 LB.	2,990 LB.	3,500 lbs.

\*Measurement may vary due to adjustable runway.

Manufacturing specifications subject to change.



## 4-Post Lift Comparison Guide

	<b>Atlas Pro OF14K</b>
Capacity	14,000 LB.
Lifting Height	71 1/8" (5' 11 1/8")
Overall Width of Columns (With Motor)	138 1/2" (11' 6 1/2") 290" (24' 2")
Overall Length (w/ Approach Ramps)	290" (24' 2")
4-Wheel Alignment Wheelbase	Maximum 155" (12' 11") Minimum 81" (6' 9")
2-Wheel Alignment Wheelbase	Maximum 218" (18' 2")
Length Between Columns	227" (18' 11")
Runway Length	243" (20' 3")
Runway Width	20 1/4" (1' 8 1/4")
Thickness of Runway	8 1/4"
Width Between Runways	42 5/8" (3' 6 5/8")
Width Between Runway Rails	38 7/8" (3' 2 7/8")
Outside Runway to Outside Runway	83 1/4" (6' 11 1/4")
Clearance Under Runways	63 1/8" (5' 3 1/8")
Clearance Between columns	Rear: 118" (9' 10") Front: 117" (9' 9")
Height of Columns	Rear: 85 3/4" (7' 1 3/4") Front: 91" (7' 7")
Maximum Wheel Base	230" (19' 2")
Drive Thru	100" (8' 4")
Motor	220V 1 Phase
Warranty	1 Year Structural, 1 Year Hydraulic
Shipping Weight	2,990 LB.

Manufacturing specifications subject to change.